

340 - Keyboard Verlabelung Manual

im Einschub (geknotet!)

im Keyboard

Flachkabel → 24 Pol - Buchse

24 Pol - Stecker → Flachkabel

16	→ 8	7 b 7	} Abfrage Sammelschienen Keyboard Port PIA B
1	7	6 b 6	
15	6	0 b 5	
2	5	5 b 4	
14	4	4 b 3	
3	3	3 b 2	} Ansteuerung Port PIA A
13	2	2 b 1	
4	1	1 b 0	
12	14	b 0	
5	9	7	
11	10	2	} Ansteuerung Port PIA A
6	11	3	
10	12	4	
7	13	5	
8	15	6	
	16	7	

1	rt	8	→	16
2	bl	7		1
3	li	6		15
4	gr	5		2
5	gn	4		14
6	ge	3		3
7	sw	2		13
8	ts	1		4
9	bt	14		12
10	ws	9		5
11	gt/ts	10		11
12	ws/ts	11		6
13	bt/ts	12		10
14	bl/rt	13		7
15	bt/gr	15		9
16	ws/rt	16		8

bl/bt 17 } Keys. DMS
ge/bt 18

ge/ws 19 } Pitch oben
ws/gr 20 } Schleifer
br/rt 21 } Wheel unten

gn/ws 22-24 } ~~frei~~
bl/ws 23
gn/bt 24

im Einsteckb (gekodet!)

im Keyboard

Flachkabel → 24 Pol - Buchse

24 Pol - Stecker → Flachkabel

16	→	8
1		7
15		6
2		5
14		4
3		3
13		2
4		1
12		14
5		9
11		10
6		11
10		12
7		13
8		15
		16

1	rt	8
2	bl	7
3	li	6
4	gr	5
5	gn	4
6	ge	3
7	sw	2
8	ts	1
9	bt	14
10	ws	9
11	gr/ts	10
12	ws/ts	11
13	bt/ts	12
14	bl/rt	13
15	bt/gr	15
16	ws/rt	16

16
1
15
2
14
3
13
4
12
5
11
6
10
7
9
8

bl/bt	17	} Keyb.	DMS
ge/bt	18		

ge/ws	19	} Pitch	oben		
ws/gr	20			Wheel	Schleifer
br/rt	21				

gn/ws	22	} frei
bl/ws	23	
gn/br	24	