

The Component Ranges RS 74 and RS 76

The Rafi full-travel keyswitches RS 74/76 are modular systems for designing individual key blocks and keyboards in the 3/4 inch (= 19.05 mm) grid.

Definitions

Momentary keyswitches

Momentary keyswitches return to their initial position after being pressed (momentary action).

Latching keyswitches

Latching keyswitches lock when actuated and are returned to their initial position when pressed again (push-push action).

Keycap materials

Keycap without legend insert: ABS

Keycap with legend insert:

- Keycap body: ABS
- Lens: PC

Keycap, n-module

A 2-module keycap f. ex. has the twofold length of a 1-module keycap.

1-module 1½-module 2-module 3-module



Contact principle

There are two contact principles:

- Mechanical (M): Cross contact (RS 74/RS 76 M)
Bridge contact (RS 76 M, illuminated)
- Contactless (C): Based on Hall IC (RS 76 C)

Soldering

The soldering temperature should not exceed 250 °C, the soldering time not be longer than 3 seconds.

Following momentary/latching keyswitches can be flow-soldered:

- Momentary/latching keyswitches with sealed bottom and sealed terminals:
 - Momentary keyswitches RS 74 M with increased ESD-strength
 - Keylock, code and rotary switches
- All momentary/latching keyswitches RS 76 C (Hall-IC)

The assembled PCB should be cleaned only by using brushing machines from the soldering side of the PCB. The cleaning agent should not exceed the component side of the PCB. Unsealed momentary/latching keyswitches (= rest of programme) can be flow-soldered, provided that an acid fluxer is used and that the whole unit is cleaned afterwards in de-ionised water.

Keylock, code and rotary switches should not be cleaned in this way.

Cleaning

Keyswitches should not be washed in freon or similar substances as a lubricant is used, otherwise the operating life of the keyswitches will be reduced.


If complete keyboards are to be cleaned by dipping, it must be remembered that the keyboard may only be dipped in the dipping solution as far as the component side of the PCB.

Features RS 74 and RS 76

	RS 74	RS 76
Degrees of protection acc. to DIN 40 050	IP 40/ IP 54	IP 40/ IP 65
Overall height	10.8/ 11.6 mm	15.5/ 15.9 mm
Full travel	2.5 mm	4 mm

Examples for Application

Example: Key block RS 74 M



Example: Keyboard RS 76



Application example: Rafi keyboard with German keycap set

Legending of keycaps

Keycaps can be legended by different methods:

Two-shot moulding

Using this method the symbol is separately manufactured from a plastic and then the appropriate keycap form is moulded round it. Advantage: The character becomes an integrated part of the keycap, thus eliminating abrasion.

All Rafi keycap sets with standard legending are manufactured by this method.

Customer-specific keycaps which are two-shot moulded have a minimum order quantity for each symbol.

Printing

Keycaps can be printed with a two-component ink on request. The abrasion of this kind of legending is very high. No abrasion will occur if in case of keycaps with replaceable legend insert, the legending is printed on a legend insert and protected by a transparent lens.

This method of legending is suitable for average volumes.

Engraving

In this highly labour intensive process the keycaps are engraved with the required symbol, then inlaid with ink. Only used for small volumes.

Laser-printing

This method of legending can be recommended when complete keyboards are required in different keyboard layouts for which Rafi will develop the respective software. The keyboards can then be legended within a short time. This method of legending is particularly recommended for average to large volumes.

Legend inserts

In the case of keycaps with replaceable legend inserts it is possible to print or engrave the legend inserts. As these inserts are protected by the lens, there can be no abrasion here either.

Contents


■ IP 40: Momentary/latching keyswitches and keycaps	5 – 68
■ IP 54: Momentary/latching keyswitches and keycaps	5 – 70
■ Legended keycap sets	5 – 72
■ Circuit diagrams	5 – 73
■ Cut-out – support plate	5 – 74

General Information

The full-travel keyswitches RS 74 M have a particularly low overall height of only 10.8/11.6 mm with a full travel of 2.5 mm. Any keyboard arrangements are possible due to the modular system in the $3/4'' = 19.05$ mm grid.

The cross contact (gold)/1 NO-contact used in the momentary/latching keyswitches ensures a high contact reliability and short bouncing times.
The **latching keyswitch** is illuminable.


Design IP 40



When ordering keycaps ≥ 2 -module, the accessories marked with *) are included in the delivery.

Note for IP 54 version: The degree of protection IP 54 is guaranteed by the use of sealing caps (spotted in the drawing). They seal up the contact system between momentary/latching keyswitch and keycap.

Design IP 54




By means of a **support plate** (see "Cut-out – Support Plate") the individual sealing caps are pressed to the keyswitch housing.

The support plate is fixed to the PCB by means of thread studs and spacers (see "Accessories").


For the protection of the sealing caps we recommend the use of covers (see "Accessories") or a covering plate.

Mom./Latching Keyswitches/Keycaps

Momentary keyswitch, non-illuminated	Order no.	Keycap, non-illuminated				Colour no. Keycap (A)			
		Order no.							
 with increased ESD-strength	3.12961.001	(A) (Legended keycap sets see page 5 – 54)	 or	1- module 5.82200.000 /colour no.	1½- module 5.82210.000 /colour no.	2- module 5.82570.000 /colour no.	3- module 5.82580.000 /colour no.	8- module 5.82590.000 /colour no.	/0754 light grey /0801 dark grey /0103 black /0305 red (only 1-module) /0406 yellow (only 1-mod.) /0505 green (only 1-mod.) /0602 blue (only 1-mod.)
Latching keyswitch, non-illuminated	Order no.	(B)	 Keycap delivered in single parts: Mat lens, legend insert, keycap body	1- module	Key- cap body	Order no.	Colour no. Keycap (B)		
(2) 	3.12960.101				light grey	5.04665.407 /colour no.	/5520 colourless white /5570 colourless light grey /5580 colourless dark grey /5511 colourless black /5523 red white /5524 yellow white /5525 green white		
					dark grey	5.04665.408 /colour no.			
					black	5.04665.402 /colour no.			
					2- mo- dule*	light grey		5.04665.447 /colour no.	
						dark grey		5.04665.448 /colour no.	
				black		5.04665.442 /colour no.			
Latching keyswitch, illuminated	Order no.	Keycap, illuminated				Colour no. Keycap (C)			
Order no.									
(3)  with integrated LED, red	3.17960.101	(C) 	1- module	5.82400.000 /colour no.		/0754 light grey /0801 dark grey /0103 black /0305 red /0406 yellow /0505 green /0602 blue			

* 2 momentary/latching keyswitches for each keycap

(1), (2)



Operating life (1): $\geq 10^7$ operations
 ESD-protection: Cover: PC
 ESD-strength: ≤ 12 kV

Switching symbol

**Mechanical construction**

Contact system and arrangement: Cross contact, 1 normally-open contact

Fixing: By soldering into the PCB

Flammability of plastic materials: UL 94 HB

Contact material: Gold-alloy
 Terminals: Soldering terminals, copper-alloy, tin-plated

Mechanical characteristics

Operating force: 0.8 N
 Full travel: 2.5 mm
 Switching travel: 1.5 ± 0.5 mm
 Robustness: ≥ 100 N

Electrical characteristics

Rated voltage: 2 ... 42 V AC/DC
 Rated current: 0.01 ... 100 mA

Rated power: ≤ 1 W

Contact resistance: ≤ 100 m Ω , when new
 ≤ 3 Ω after operating life

Insulation resistance: $\geq 10^9$ Ω
 Bouncing time: ≤ 5 ms

Further details


Ambient temp., operating: -25 $^{\circ}\text{C}$... $+70$ $^{\circ}\text{C}$
 Ambient temp., storage: -40 $^{\circ}\text{C}$... $+80$ $^{\circ}\text{C}$ (without packing)
 -40 $^{\circ}\text{C}$... $+50$ $^{\circ}\text{C}$ (with standard packing)

Environment conditions:

- Constant environment: acc. to IEC 68-2-3 and 2-30
 - Variable environment: acc. to IEC 68-2-14 and 2-33

Illumination: (3):

LED (characteristics at $T = 25$ $^{\circ}\text{C}$)
 Light intensity ($I_F = 10$ mA): > 5 mcd
 Forward voltage ($I_F = 10$ mA): typ. 2.1 V
 Forward current: 25 mA max.
 Power dissipation: 135 mW max.
 Series resistor for 5 V: 180 Ω (approx. 15 mA)




Operating life (2): $\geq 10^5$ operations
 ESD-strength: ≤ 7 kV

Switching symbol



(3)



Operating life (3): $\geq 10^5$ operations
 ESD-strength: ≤ 4 kV





Illumination with red LED (other LED colours on request)

Switching symbol



Mom./Latching Keyswitches/Keycaps

Momentary keyswitch non-illuminated	Order no.	Keycap, non-illuminated				Colour no. Keycap (A)			
(1)	3.12961.211	(A) (Legended keycap sets see page 5-54)		or	1- module	5.82200.000 /colour no.	/0754 light grey /0801 dark grey /0103 black /0305 red (not for 3- and 8-mod.) /0406 yellow (not for 3- and 8-mod.) /0505 green (not for 3- and 8-mod.) /0602 blue (not for 3- and 8-mod.)		
1½- module					5.82210.000 /colour no.				
2- module					5.82470.000 /colour no.				
3- module					5.82480.000 /colour no.				
8- module					5.82490.000 /colour no.				
Latching keyswitch, non-illuminated	Order no.	(B)		Keycap delivered in single parts: Mat lens, legend insert, keycap body	1- module	Keycap body	Order no.	Colour no. Keycap (B)	
(2)	3.12960.311					light grey	5.04665.407 /colour no.	Lens Legend insert /5520 colourless white /5570 colourless light grey /5580 colourless dark grey /5511 colourless black /5523 red white /5524 yellow white /5525 green white	
						dark grey	5.04665.408 /colour no.		
						black	5.04665.402 /colour no.		
						2- module	light grey		5.04665.417 /colour no.
							dark grey		5.04665.418 /colour no.
							black		5.04665.412 /colour no.
Latching keyswitch, illuminated	Order no.	Keycap, illuminated				Colour no. Keycap (C)			
(3)	3.17960.351	(C)		or	1- module	5.82400.000 /colour no.		/0754 light grey /0801 dark grey /0103 black /0305 red /0406 yellow /0505 green /0602 blue	
		(D)		Delivered in single parts	Keycap body	Order no.	Colour no. Keycap (D)		
					light grey	5.04665.467 /colour no.	see (2)		
					dark grey	5.04665.468 /colour no.			
					black	5.04665.462 /colour no.			

(1), (2), (3) 	Operating life (1): $\geq 10^6$ operations ESD-strength: ≥ 10 kV Switching symbol 	Mechanical construction Contact system and arrangement: 1 normally-open contact Fixing: By soldering into the PCB Flammability of plastic materials: UL 94 HB Contact material: Gold-alloy Terminals: Soldering terminals, copper-alloy, tin-plated
	Operating life (2): $\geq 10^5$ operations ESD-strength: ≥ 10 kV Switching symbol 	Mechanical characteristics Operating force: 1 N Full travel: 2.5 mm Switching travel: 1.5 ± 0.5 mm Robustness: ≥ 100 N Electrical characteristics Rated voltage: 2 ... 42 V AC/DC Rated current: 0.01 ... 100 mA AC/DC Rated power: ≤ 1 W Contact resistance: ≤ 100 mΩ, when new ≤ 3 Ω after operating life Insulation resistance: $\geq 10^9$ Ω Bouncing time: ≤ 5 ms
	Operating life (3): $\geq 10^5$ operations ESD-strength: ≥ 4 kV Illumination with red LED (other LED colours on request) Switching symbol 	Further details Ambient temp., operating: -25 $^{\circ}\text{C}$... $+70$ $^{\circ}\text{C}$ Ambient temp., storage: -40 $^{\circ}\text{C}$... $+80$ $^{\circ}\text{C}$ (without packing) -40 $^{\circ}\text{C}$... $+50$ $^{\circ}\text{C}$ (with standard packing) Environment conditions: - Constant environment: acc. to IEC 68-2-3 and 2-30 - Variable environment: acc. to IEC 68-2-14 and 2-33 Illumination (3): LED (characteristics at $T = 25$ $^{\circ}\text{C}$) Light intensity ($I_F = 10$ mA): > 20 mcd Forward voltage ($I_F = 10$ mA): typ. 2.1 V Forward current: 25 mA max. Power dissipation: 135 mW max. Series resistor for 5 V: 180 Ω (approx. 15 mA)


Circuit Diagrams IP 40/54

For 1- and 1½-module keycaps and keycap (B) 2-module, IP 40 with 2 momentary/latching keyswitches:

non-illuminated

with LED


View on component side



For 1- and 1½-module keycaps no boreholes are necessary

For 2-, 3- and 8-module keycaps IP 40 (keycap (B) 2-module, IP 40 see above):


Hole diam. 2
No through-plating



Keycap	L 1 mm	L 2 mm
2-module	30.48	22.86
3-module	38.10	30.48
8-module	133.35	120.65

In the case of 2-, 3- and 8-module keycaps additional boreholes have to be provided for the accessories

For 2-, 3- and 8-module keycaps IP 54:



Keycap	L 1 mm	L 2 mm
2-module	23.495	33.655
3-module	33.02	43.18
8-module	128.27	138.43

In the case of 2-, 3- and 8-module keycaps additional boreholes have to be provided for the accessories

Important note:


All the circuit diagrams apply to the horizontal position of the keycap symbols. If the symbols are to be rotated by 90 degrees, the keyswitch must be mounted accordingly i.e. rotated by 90 degrees.

For keycaps ≥ 2 -module the momentary/latching keyswitch has to be soldered into rotated by 90 degrees, too.


PCB Keyswitches – Full-Travel

Cut-out – Support Plate IP 54

For 1-module keyswitches



For multi-module keyswitches



Keycap	$L \pm 0.05$
2-module	28.30
3-module	38.10
8-module	133.35

Contents

RS 76 M/C

■ RS 76 M: Momentary/latching keyswitches IP 40/65	5 – 78
■ RS 76 C: Momentary/latching keyswitches IP 40/65	5 – 80
□ Specific technical data	5 – 82
□ Examples for application	5 – 83
■ RS 76 M/C: Dimensional drawings/hole patterns	5 – 84
■ Blank keycaps	5 – 86
□ Non-illuminated	5 – 86
Without legend insert	
With replaceable legend insert	
□ Illuminated	5 – 87
Without legend insert	
With replaceable legend insert	
□ With protective collar IP 65, Illuminated / non-illuminated	5 – 88
■ Legended keycaps	5 – 89
■ Legended keycap sets	5 – 90
■ Accessories	5 – 94

General Information

The full-travel keyswitches RS 76 with an overall height of 15.5/15.9 mm and a full-travel of 4 mm excel by their high degree of operating comfort.

Any key blocks are possible due to the modular system in the $3/4'' = 19.05$ mm grid.

The momentary/latching keyswitches are available with the degrees of protection IP 40 and IP 65 as well as with two different contact principles:

Mechanical RS 76 M

Momentary keyswitch, non-illuminated: Cross contact
Momentary/latching keyswitch, illuminated: Bridge contact

A gold-alloy as contact material together with the construction of the systems provide for a high contact reliability, low contact resistances and short bouncing times.

Contactless RS 76 C


Momentary keyswitch, non-illuminated;
Latching keyswitch, illuminated: Contactless Hall IC

Due to the use of a solid state switch in Hall-IC technology a bounce- and wearfree switching as well as a long operating life are achieved.

Operation: When the keyswitches are actuated, the position of a permanent magnet is altered in relation to the Hall IC, thereby generating an output signal.

The use of these keyswitches is therefore particularly recommended under severe environmental influences and high stress conditions.

Design IP 40



No. Description

- 1.1 Momentary keyswitch RS 76 C
- 1.2 Momentary/latching keyswitch RS 76 C with LED
- 1.3 Momentary keyswitch RS 76 M
- 1.4 Momentary/latching keyswitch RS 76 M with LED
- 2 Keycap, 1- resp. multi-module
- 3 Keycap with nail protection, 1- resp. multi-module
- 5 Keycap, illuminated
- 6 Keycap, illuminated
- 7 Keycap, illuminated


- 8 LED
- 9 Spacer for LED (for RS 76 C only)
- 10.1 Plunger for multi-module keycaps*
- 10.2 Sleeve for multi-module keycaps*
- 10.3 Metal lever for multi-module keycaps*
- 10.4 Bearing bracket for multi-module keycaps*
- 11 Covers

* These parts are included as a complete packet in the delivery of keycaps ≥ 2 -module.

Design IP 65

The individual keyswitches are sealed with a sealing cap and a support plate. The support plate can be manufactured either by Rafi or by the customer. For the protection of the sealing caps we recommend the use of covers (see "Accessories") or a covering plate (not shown in the drawing).

The accessories delivered with orders of IP 65 momentary/latching keyswitches as well as the assembly sequence can be seen from the below drawing.




No.	Description
1	Momentary/latching keyswitch RS 76 C
1.1	Sealing ring
1.2	Coupling piece
1.3	Sealing cap
2	Spacer
3	Support plate
4	Keycap
5	Use spring washer
6	Torque for fixing 0.4...0.6 Nm

The parts 1.1 – 1.3 are included with no. 1 in deliveries of momentary/latching keyswitches IP 65.

Assembly sequence:

- Pre-assemble coupling piece (no. 1.2) and sealing cap (no. 1.3).
- Insert this in support plate (no. 3).
- Insert sealing ring (no. 1.1) from below in the pre-assembled sealing cap.
- Assemble pre-assembled sealing cap with spacers (no. 2) and with PCB completely (coupling piece shall be snapped in).

Multi-module keycap (Example: 8-module)



* These parts are included as a complete packet in the delivery of keycaps ≥ 2-module.

Momentary/Latching Keyswitches

Momentary keyswitch, non-illuminated	Illumination	Order no. IP 40		Order no. IP 65	
		Operating force		Operating force	
		0.9 N	1.4 N*	1.1 N	1.6 N*
(1) 	-	3.13002.502	3.13002.512	3.13012.502	3.13012.512
(2)  with diode		3.13005.001	3.13005.011	3.13012.001	3.13012.011
Momentary keyswitch, illuminated	Illumination	Order no. IP 40			
		Operating force			
		1 N		1.4 N*	
(3) 	LED	-	3.13002.102/0000	3.13002.107/0000	
		red**	3.13002.102/1350	3.13002.107/1350	
		green**	3.13002.102/1550	3.13002.107/1550	
		yellow**	3.13002.102/1450	3.13002.107/1450	
(4) 	LED	-	3.13002.022/0000	-	
		red**	3.13002.022/1350		
		green**	3.13002.022/1550		
		yellow**	3.13002.022/1450		


* Recommended for multi-module keycaps.



** LED included in delivery contents.

(1) – (4): IP 40

Example for keyswitches

(1, 2) IP 65:



	Non-illuminated		Illuminated		
	(1) Momentary keyswitch	(2) Mom. keys. with diode	(3) Momentary keyswitch	(4) Latching keyswitch	
					
Mechanical construction					
Contact system and arrangement	Cross contact, 1 NO-contact		Bridge contact, 1 NO-contact		
Fixing	By soldering into the PCB				
Materials	Keycap: ABS, housing: PBTP, actuator: POM				
Flammability of plastic materials	UL 94 HB				
Contact material	Gold alloy				
Terminals	Solder terminals, tin-plated				
Illumination	-		By LED		
Mechanical characteristics					
Max. operating force IP 40 (65) in N	0.9/1.4 (1.1/1.6)		1/1.4	1	
Full travel	4 mm				
Switching travel	1.5 – 2.8 mm				
Robustness	≥ 100 N				
Electrical characteristics					
Rated voltage	2 ... 42 V	3 ... 42 V	2 ... 42 V		
Rated current	0.01 ... 100 mA	0.01 ... 100 mA	0.01 ... 100 mA		
Rated power	≤ 1 W				
Contact resistance, when new	≤ 100 mΩ	*	≤ 200 mΩ		
after operating life	≤ 3 Ω	*	≤ 3 Ω		
Insulation resistance	≥ 10 ⁹ Ω				
ESD-strength	≤ 8 kV				
Bouncing time	≤ 5 ms		≤ 10 ms		
LED (characteristics at T = 25 °C)	-		red	green	yellow
- Wavelength	-		635 nm	560 nm	585 nm
- Light intensity (I _F = 10 mA)	-		≥ 15 mcd	≥ 10 mcd	≥ 15 mcd
- Forward voltage (I _F = 10 mA)	-		typ 2.1 V		
- Forward current	-		30 mA max.		
- Power dissipation	-		120 mW max.		
- Series resistor for 5 V**	-		270 Ω (approx. 11 mA)		
Operating life (operations)					
	≥ 10 ⁷			≥ 10 ⁵	
Further details					
Ambient temperature, operating	- 25 °C ... + 70 °C				
Ambient temperature, storage					
- Without packing	- 40 °C ... + 80 °C				
- With standard packing	- 40 °C ... + 50 °C				
Environment conditions	Constant env.: acc. to IEC 68-2-3 and 2-30; Variable env.: acc. to IEC 68-2-14 and 2-33				

* Contact resistance cannot be measured due to integrated LED

** Recommendation

Momentary/Latching Keyswitches


Momentary keyswitch, non-illuminated	Illumination	Order no. IP 40		Order no. IP 65	
		Operating force		Operating force	
		0.7 N	1 N*	1 N	1.3 N*
(1) 	–	3.13001.010	3.13001.210	3.13011.010	3.13011.210
Momentary keyswitch, illuminated	Illumination	Order no. IP 40		Order no. IP 65	
		Operating force		Operating force	
		0.7 N		1.1 N	
(2) 	LED	–	3.13001.110/0000	3.13011.110/0000	
		red**	3.13001.110/1350	3.13011.110/1350	
		green**	3.13001.110/1550	3.13011.110/1550	
		yellow**	3.13001.110/1450	3.13011.110/1450	
Latching keys., illuminated (3) 	LED	–	3.13001.130/0000	3.13011.130/0000	
		red**	3.13001.130/1350	3.13011.130/1350	
		green**	3.13001.130/1550	3.13011.130/1550	
		yellow**	3.13001.130/1450	3.13011.130/1450	

* Recommended for multi-module keycaps.

** LED and spacer included in delivery contents.

(1) – (3): IP 40

Example for momentary/latching keyswitches IP 65:




	Non-illuminated	Illuminated		
Mechanical construction	(1) Momentary keyswitch	(2) Mom. keyswitch	(3) Latching keysw.	
Contactless switching system	Hall IC, 1 enable input, 1 transistor output NPN			
Fixing	By soldering into the PCB			
Materials	Keycap: ABS, housing: PBTP, actuator: POM			
Flammability of plastic materials	UL 94 HB			
Terminals	Solder terminals, tin-plated			
Illumination	–	By LED		
Mechanical characteristics				
Max. operating force IP 40 (65) in N	0.7/1.0 (1.0/1.3)		0.7 (1.0)	
Full travel	4 mm			
Switching travel – on	1.5 ... 2.8 mm			
– off	0.8 ... 2.4 mm			
Robustness	≥ 100 N			
Electrical characteristics				
Supply voltage	4.75 ... 5.25 V = *			
Supply current	≤ 0.5 mA at U _{IL} = 0 V		≤ 5 mA at U _{IH} = + 5 V	
Input voltage (F)	U _{IL} = 0 ≤ 0.4 V		U _{IH} = 2.4 V ≤ 5.25 V	
Output load current (Q)	≤ 16 mA			
Output residual current (Q)	≤ 10 µA			
Output saturation voltage (Q)	≤ 0.4 V (at 16 mA)			
Output switching times (Q)	at T _U = 25 °C	at T _U = 50 °C	at T _U = 70 °C	
t _{PHL}	3 µs	7 µs	10 µs	
(see pulse diagram) t _{PLH}	4 µs	5 µs	6 µs	
t _{THL}	1 µs	1,5 µs	2,5 µs	
t _{TLH}	2 µs	2,5 µs	3 µs	
ESD-strength	≤ 9 kV		≤ 7 kV	
LED (characteristics at T = 25 °C)	–	red	green	yellow
– Wavelength (approx.)	–	635 nm	560 nm	585 nm
– Light intensity (I _F = 10 mA)	–	≥ 15 mcd	≥ 10 mcd	≥ 15 mcd
– Forward voltage (I _F = 10 mA)	–	typ. 2.1 V		
– Forward current	–	30 mA max.		
– Power dissipation	–	120 mW max.		
– Series resistor for 5 V**	–	270 Ω (approx. 11 mA)		
Operating life (mechanical)	≥ 10 ⁸		≥ 10 ⁸	≥ 10 ⁵
Reliability of Hall IC	λ = 2.5 x 10 ⁻⁷ h ⁻¹ (at T _U = 25 °C)			
Further details				
Ambient temp., operating	0 °C ... 70 °C			
Ambient temp., storage	Without packing: – 40 °C ... + 80 °C, with standard packing: – 40 °C ... + 50 °C			
Environment conditions	Constant env.: acc. to IEC 68-2-3 and 2-30; Variable env.: acc. to IEC 68-2-14 and 2-33			

* Other supply voltages on request


** Recommendation

Specific Technical Data

Output pulse diagram, dynamic characteristics (max.)		Tw = 25 °C	Tw = 50 °C	Tw = 70 °C
Turn-on delay time	t_{PHL}	3 μ s	7 μ s	10 μ s
Turn-off delay time	t_{PLH}	4 μ s	5 μ s	6 μ s
Fall/rise time	t_{TLH}	2 μ s	2.5 μ s	3 μ s
	t_{THL}	1 μ s	1.5 μ s	2.5 μ s




Block diagram
Hall IC




STATIC with ENABLE INPUT

Examples for Application


Driving of logic components




Indication of logical states




Driving of a PNP transistor



Use as static key with open collector output. Output transistor (NPN) is conductive when actuated.



Use in keyboards



Dimensional Drawing

Momentary/ latching keyswitches with keycap			
IP 40			
IP 65			

Hole Patterns

	For 1 – 1¼-module keycaps (view on component side)	
	Momentary keyswitch, non-illuminated	Momentary/latching keyswitch, illuminated
RS 76 M	● Boreholes ø 1.1 Borehole ø 4.8 no through-plating	● Boreholes ø 1.1
RS 76 C	● Boreholes ø 1.1 Borehole ø 4.8 no through-plating	● Boreholes ø 1.1


The hole patterns apply to the horizontal position of the keycaps only. Should they be in a vertical position, the

momentary/latching keyswitches must be mounted accordingly, i.e. rotated by 90°.

Hole Patterns

The hole patterns apply to the horizontal position of the keycaps only. Should they be in a vertical position, the

momentary/latching keyswitches must be mounted accordingly, i.e. rotated by 90°.




Keycap	L mm
2-module	25.40
3-module	30.48
8-module	125.73


Important note: In the case of 2-, 3- and 8-module keycaps, additional holes must be provided for the accessories. In the case of keycaps < 2-module, neither accessories nor holes are required.

Support Plates IP 65

1 – 1¼-module




2-, 3- and 8-module



Keycap	L mm
2-module	25.40
3-module	30.48
8-module	125.73

Keycaps, non-illuminated

Keycap, without legend insert	Degree of protection	Order no. 5.82--0.000 / colour no.									Colour no. Keycap
		1-module	1¼-module	1½-module	1¾-module	2-module	3-module	L-shape key*	8-module	2-module vertical	
(1)  (1-module)	IP 40					-70	-71	-72	-73	-74	/0710 light beige /0242 light grey /0801 dark grey /0152 charcoal grey
	IP 65	-00	-07	-01	-08	-75	-76	-77	-78	-79	
(2)  (1-module)	Order no. 5.80--0.000 / colour no.										only 1-module /0406 yellow /0505 green /0602 blue /0305 red
	Degree of protection	1-module	1¼-module	1½-module	1¾-module	2-module	3-module	L-shape key*	8-module	2-module vertical	
	IP 40					-70	-71	-72	-73	-74	
	IP 65	-00	-07	-01	-08	-75	-76	-77	-78	-79	

From keycaps (1) and (2) keycap sets, two-shot moulded are available (see RS 76 M/C "Keycap Sets").
 Ordering example for (1): Keycap without legend insert IP 65, 1-module, light grey, order no. 5.82000.000/0242
 In the case of keycaps $\geq$ 2-module, the necessary accessories are included in the delivery.

* Size of L-shape key, see "Keycap Sets" – Keycap Set "International"

Keycap, with replaceable legend insert	Degree of protection	Colour keycap body	Order no. 5.04665.--- /colour no.				Colour no. Keycap	
			1-module	1½-module	2-module	3-module		
(3)  (1-module)	IP 40	light beige	.222	.242	.262	.272	Lens /5520 colourless /5572 colourless /5580 colourless /5510 colourless /5522 colourless /5523 red /5524 yellow /5525 green	Legend insert white light beige dark grey charcoal grey light grey white white white
		dark grey	.228	.248	.268	.278		
		charcoal grey	.221	.241	.261	.271		
		light grey	.230	.250	.270	.280		
	IP 65	light beige	.222	.242	.662	.682		
		dark grey	.228	.248	.668	.688		
		charcoal grey	.221	.241	.661	.681		
		light grey	.230	.250	.669	.689		


With order no. following **single parts** are delivered: lens mat, legend insert, keycap body as well as with keycaps $\geq$ 2-module the necessary accessories.

Keycaps, illuminated

Keycap, without legend insert	Order no.	Colour no.	
	1-module		
(1) 	5.82110.000 / colour no.	/0801 dark grey /0152 charcoal grey /0710 light beige /0242 light grey	LED light bar is colourless transparent.

Keycap, with replaceable legend insert	Degree of protection	Colour Keycap body	Order no. 5.04665.---- /colour no.			Colour no. Keycap																										
			1-module	1½-module	1¾-module																											
(2)  (1½-module)	IP 40/65	light beige	.522	.542	.552	(2) – (4) <table><tr><th>Lens</th><th>Legend insert</th></tr><tr><td>/5520</td><td>colourless</td><td>white</td></tr><tr><td>/5572</td><td>colourless</td><td>light beige</td></tr><tr><td>/5580</td><td>colourless</td><td>dark grey</td></tr><tr><td>/5510</td><td>colourless</td><td>charcoal grey</td></tr><tr><td>/5522</td><td>colourless</td><td>light grey</td></tr><tr><td>/5523</td><td>red</td><td>white</td></tr><tr><td>/5524</td><td>yellow</td><td>white</td></tr><tr><td>/5525</td><td>green</td><td>white</td></tr></table>	Lens	Legend insert	/5520	colourless	white	/5572	colourless	light beige	/5580	colourless	dark grey	/5510	colourless	charcoal grey	/5522	colourless	light grey	/5523	red	white	/5524	yellow	white	/5525	green	white
Lens		Legend insert																														
/5520		colourless	white																													
/5572		colourless	light beige																													
/5580	colourless	dark grey																														
/5510	colourless	charcoal grey																														
/5522	colourless	light grey																														
/5523	red	white																														
/5524	yellow	white																														
/5525	green	white																														
	dark grey	.528	.548	.558																												
	charcoal grey	.521	.541	.551																												
	light grey	.530	.550	.560																												
(3)  (1-module)	IP 40/65	light beige	.912		.932																											
		dark grey	.918		.938																											
		charcoal grey	.911		.931																											
		light grey	.920		.940																											
(4)  (1½-module)	Degree or protection	Colour Keycap body	Order no. 5.04665.---- /colour no.																													
			1-module	1½-module	2-module	3-module																										
	IP 40	light beige	.162	.182	.202	.212	With order no. following single parts are delivered: (2) and (4): Mat lens, legend insert, diffuser foil, keycap body. When assembling, ensure that the shiny side of the diffuser foil lies on the keycap body. (4): Keycaps ≥ 2-module, necessary accessories are included. (3): Mat lens, legend insert, keycap body.																									
		dark grey	.168	.188	.208	.218																										
		charcoal grey	.161	.181	.201	.211																										
		light grey	.170	.190	.210	.220																										
	IP 65	light beige	.162	.182	.672	.692																										
		dark grey	.168	.188	.678	.698																										
		charcoal grey	.161	.181	.671	.691																										
		light grey	.170	.190	.679	.699																										


Keycaps with Protective Collar IP 65

Keycap, complete	Version	Order no.	Colour no. Protective collar
 consisting of: - colourless lens - white legend insert - diffuser foil (only with illuminated version)* - keycap body - actuator spring - protective collar (delivered in single parts)	illuminated	5.04665.991 /colour no.	/0710 light beige /0801 dark grey /0152 charcoal grey /0242 light grey
	non-illuminated	5.04665.992 /colour no.	



The Rafi keycaps with protective collars provide protection against accidental actuation according to the requirements of the trading associations. These keycaps may be mounted anywhere on the keyboard (3/4" grid = 19.05 mm).

* When assembling, ensure that the shiny side of the diffuser foil lies on the keycap body.

Construction:



Legended Keycaps, two-shot moulded

Keycaps, opaque, with nail protection		Order no. IP 40/IP 65	Keycaps, opaque		Order no. IP 40/IP 65
 1 ¼-module		5.80071.184/colour no.	 1 ¼-module		5.82071.184/colour no.
 1 ½-module		5.80010.801/colour no.	 1 ½-module		5.82010.801/colour no.
 1 ¾-module		5.80080.502/colour no.	 1 ¾-module		5.82080.502/colour no.
 1 ¾-module		5.80083.703/colour no.	 1 ¾-module		5.82083.703/colour no.
 2-module		IP 40: 5.80700.036/colour no. IP 65: 5.80750.036/colour no.	 2-module		IP 40: 5.82700.036/colour no. IP 65: 5.82750.036/colour no.
 2-module		IP 40: 5.80747.290/colour no. IP 65: 5.80797.290/colour no.	 2-module		IP 40: 5.82747.290/colour no. IP 65: 5.82797.290/colour no.
 L-shape key		IP 40: 5.80721.578/colour no. IP 65: 5.80771.578/colour no.	 L-shape key		IP 40: 5.82721.578/colour no. IP 65: 5.82771.578/colour no.
Colour no.	Keycap	light beige	dark grey	charcoal grey	light grey
	Symbol	brown	white	white	black
	Reference code	/9740	/9820	/9121	/9216

Legended Keycap Sets, two-shot moulded

ESC	1	2	3	4	5	6	7	8	9	0	*	=	@	\
TAB	Q	W	E	R	T	Y	U	I	O	P	~	LINE FEED		
CTRL	CAPS LOCK	A	S	D	F	G	H	J	K	L	+	{	}	
BRK	SHIFT	Z	X	C	V	B	N	M	<	>	?	SHIFT	DEL	
SHIFT LOCK														

Keycap set, International	Degree of pro- tection*	Colour	Order no.			
		Keycap	light beige	dark grey	charcoal grey	light grey
		Symbol	brown	white	white	black
(1)		IP 40	5.00999.382	5.00999.396	5.00999.408	5.00999.800
		IP 65	5.00999.802	5.00999.803	5.00999.804	5.00999.805
(2)		IP 40	5.00999.372	5.00999.390	5.00999.402	5.00999.801
		IP 65	5.00999.806	5.00999.807	5.00999.808	5.00999.809

For keycaps ≥ 2 -module the necessary accessories are included.

* The keys "CAPS LOCK" and "SHIFT LOCK" are illuminated with RS 76 M IP 40 version and not illuminated with RS 76 M IP 65 version.

3	0	ß	>	* +	<	Ü	Ö	Ä	;	:	=	^ #
---	---	---	---	--------	---	---	---	---	---	---	---	--------

Keycap set, German	Degree of pro- tection	Colour	Order no.			
		Keycap	light beige	dark grey	charcoal grey	light grey
		Symbol	brown	white	white	black
(1)	IP 40/65		5.00999.384	5.00999.398	5.00999.410	5.00999.845
(2)			5.00999.374	5.00999.392	5.00999.404	5.00999.846

Legended Keycap Sets, two-shot moulded

7	8	9	—	*
4	5	6	+	=
1	2	3	ENTER	÷
,	0	.		×
				%

Keycap set Numerical key block	Degree of pro- tection	Colour	Order no.			
		Keycap	light beige	dark grey	charcoal grey	light grey
		Symbol	brown	white	white	black
(1) 	IP 40		5.00999.387	5.00999.401	5.00999.413	5.00999.812
	IP 65		5.00999.814	5.00999.815	5.00999.816	5.00999.817
(2) 	IP 40		5.00999.377	5.00999.395	5.00999.407	5.00999.813
	IP 65		5.00999.818	5.00999.819	5.00999.820	5.00999.821

For keycaps ≥ 2-module the necessary accessories are included.

F1	F2	F3	F4	F5	F6	F7	F8	F9	F10	F11	F12
----	----	----	----	----	----	----	----	----	-----	-----	-----

Keycap set Function key block	Degree of pro- tection	Colour	Order no.			
		Keycap	light beige	dark grey	charcoal grey	light grey
		Symbol	brown	white	white	black
(1) 	IP 40/65		5.00999.522	5.00999.523	5.00999.521	5.00999.822
(2) 			5.00999.547	5.00999.548	5.00999.546	5.00999.823

Legended Keycap Sets, two-shot moulded


A	B	C	D	E	F	G	H	I	J	K	L	M
N	O	P	Q	R	S	T	U	V	W	X	Y	Z

Keycap set A – Z	Degree of pro- tection	Colour	Order no.			
		Keycap	light beige	dark grey	charcoal grey	light grey
		Symbol	brown	white	white	black
(1) 	IP 40/65		5.00999.501	5.00999.502	5.00999.500	5.00999.824
(2) 			5.00999.526	5.00999.527	5.00999.525	5.00999.825

1	2	3	4	5	6	7	8	9	0
---	---	---	---	---	---	---	---	---	---


Keycap set 0 – 9	Degree of pro- tection	Colour	Order no.			
		Keycap	light beige	dark grey	charcoal grey	light grey
		Symbol	brown	white	white	black
(1) 	IP 40/65		5.00999.505	5.00999.506	5.00999.504	5.00999.826
(2) 			5.00999.530	5.00999.531	5.00999.529	5.00999.827

Legended Keycap Sets, two-shot moulded





Keycap set Cursor	Degree of pro- tection	Colour	Order no.			
		Keycap Symbol	light beige brown	dark grey white	charcoal grey white	light grey black
(1) 	IP 40/65		5.00999.828	5.00999.829	5.00999.830	5.00999.831
(2) 			5.00999.832	5.00999.833	5.00999.834	5.00999.835


MF 2 Keycap set with Windows keys and Euro-Symbol	Degree of pro- tection	Keycap set	Order no.	The colour of the keycaps for the alphabetic and numeric key blocks is lighter than the colour of the function keys. The necessary accessories for keycaps bigger than 1¼ units are included. The keycap set also includes three LED indicator fields with green LEDs (Num, ⇄, Scroll). Photo of German layout see page 5 – 65.
(3) 	IP 40	International	5.00999.890	
		German	5.00999.891	




Other keycap sets as well as individual keycaps on request.


Covers for Keyboard Systems

RS 74 M (IP 40)	Dimensional drawing	Order no. 5.04520.----				Colour no.
		1/4-module	1/2-module	3/4-module	1-module	
(1)  (1/4-module)	1-module  Adhesive tape	.181 /colour no.	.182 /colour no.	.183 /colour no.	.184 /colour no.	/0754 light grey /0801 dark grey /0103 black
(2)  (1/2-module)	1-module  Adhesive tape	.171 /colour no.	.172 /colour no.	.173 /colour no.	.174 /colour no.	

RS 76 M/C (IP 40)	Dimensional drawing	Order no. 5.04520.----				Colour no.
		1/4-module	1/2-module	3/4-module	1-module	
(3)  (3/4-module)	1-module  Adhesive tape	.171 /colour no.	.172 /colour no.	.173 /colour no.	.174 /colour no.	/0801 dark grey /0152 charcoal grey /0710 light beige /0242 light grey

RS 76 M/C (IP 40) with LED	Hole pattern PCB	Order no. (1-module, colour: light beige)
(4)  		5.04520.268 (LED red) 5.04520.269 (LED green)

Keycap Extractor

Keycap extractor	Order no.
(1) 	5.05800.014

Spacers

For support plate RS 74 M – IP 54	Order no.	Length	For support plate RS 76 – IP 65	Order no.	Length
(2) 	5.30109.006	3.8 mm	(3) 	5.30759.044	10.25 mm

Snap-in Lenses – RS 76 IP 40

Snap-in lens, 1-module, non-illuminated	Frame colour	Order no. 5.04665.----	Colour no.		
(4) 	light beige	.302 /colour no.	Lens Legend insert /5520 colourless white /5572 colourless light beige /5580 colourless dark grey /5510 colourless charcoal grey /5522 colourless light grey /5523 red white /5524 yellow white /5525 green white		
	dark grey	.308 /colour no.			
	charcoal grey	.301 /colour no.			
	light grey	.310 /colour no.			
Snap-in lens, 1-module, illuminated	Frame colour	Order no. 5.04665.----			
(5) 	light beige	.312 /colour no.			
	dark grey	.318 /colour no.			
	charcoal grey	.311 /colour no.			
	light grey	.320 /colour no.			

The snap-in lenses have the same external dimensions as a 1-module cover.




The circuit diagram of an illuminated RS 76 M or an illuminated RS 76 C keyswitch must be provided on the PCB. The snap-in lens is engaged in the 4.8 mm hole.

Following single parts are delivered:




(4): Mat lens, legend insert, frame

(5): Mat lens, legend insert, diffuser foil, frame

Keylock Switches IP 54

Keylock switch	Rotating angle	Key removal position	Colour	Order no.	Accessory key
	 1 x 90° latching with stop	0	charcoal grey	3.13026.001	5.58007.001
			dark grey	3.13026.201	
			light beige	3.13026.401	
			light grey	3.13026.501	
		0 + 1	charcoal grey	3.13026.006	
			dark grey	3.13026.206	
			light beige	3.13026.406	
			light grey	3.13026.506	
	 2 x 90° latching with stop	0	charcoal grey	3.13026.011	5.58008.001
			dark grey	3.13026.211	
			light beige	3.13026.411	
			light grey	3.13026.511	
		0 + 1 + 2	charcoal grey	3.13026.016	
			dark grey	3.13026.216	
			light beige	3.13026.416	
			light grey	3.13026.516	
	 3 x 90° latching with stop	0	charcoal grey	3.13026.021	5.58009.001
			dark grey	3.13026.221	
			light beige	3.13026.421	
			light grey	3.13026.521	
		0 + 1 + 2 + 3	charcoal grey	3.13026.026	
			dark grey	3.13026.226	
			light beige	3.13026.426	
			light grey	3.13026.526	
	 4 x 90° latching without stop	0	charcoal grey	3.13026.031	5.58010.001
			dark grey	3.13026.231	
			light beige	3.13026.431	
			light grey	3.13026.531	
		0 + 1 + 2 + 3	charcoal grey	3.13026.036	
			dark grey	3.13026.236	
			light beige	3.13026.436	
			light grey	3.13026.536	
	 2 x 90° latching with stop	0	charcoal grey	3.13026.601	5.58008.001
			dark grey	3.13026.701	
			light beige	3.13026.801	
			light grey	3.13026.851	
		0 + 1 + 3	charcoal grey	3.13026.606	
			dark grey	3.13026.706	
			light beige	3.13026.806	
			light grey	3.13026.856	
	 1 x 40° momentary	0	charcoal grey	3.13026.041	5.58007.001
			dark grey	3.13026.241	
			light beige	3.13026.441	
			light grey	3.13026.541	
	 2 x 40° momentary	a	charcoal grey	3.13026.611	
			dark grey	3.13026.711	
			light beige	3.13026.811	
			light grey	3.13026.861	
Accessories: Round ring 5.30120.015 Adapter for 90° assembly 5.00642.008					



Keylock Switches IP 54

Keylock switch	Rotating angle	Key removal position	Colour	Order no.
		0	charcoal grey	3.13009.001
			dark grey	3.13009.004
			light beige	3.13009.005
			light grey	3.13009.006
	1 x 90° latching with stop	0 + 1	charcoal grey	3.13009.031
			dark grey	3.13009.034
			light beige	3.13009.035
			light grey	3.13009.036
		0 + 2	charcoal grey	3.13009.101
			dark grey	3.13009.104
			light beige	3.13009.105
			light grey	3.13009.106
	2 x 90° latching with stop	0 + 1 + 2	charcoal grey	3.13009.131
			dark grey	3.13009.134
			light beige	3.13009.135
			light grey	3.13009.136
		0 + 2	charcoal grey	3.13009.201
			dark grey	3.13009.204
			light beige	3.13009.205
			light grey	3.13009.206
	3 x 90° latching with stop	0 + 1 + 2 + 3	charcoal grey	3.13009.231
			dark grey	3.13009.234
			light beige	3.13009.235
			light grey	3.13009.236
		0 + 2	charcoal grey	3.13009.301
			dark grey	3.13009.304
			light beige	3.13009.305
			light grey	3.13009.306
	4 x 90° latching without stop	0 + 1 + 2 + 3	charcoal grey	3.13009.331
			dark grey	3.13009.334
			light beige	3.13009.335
			light grey	3.13009.336




Accessories:
 Round ring 5.30120.015
 Adapter for 90° assembly 5.00642.008
 Key 5.58006.801

PCB Keyswitches – Supplements



Priority Keylock Switches IP 54

Priority keylock switch	Rotating angle	Key removal position	Colour	Order no.
(1)  Accessories: Round ring 5.30120.015 Adapter for 90° assembly 5.00642.008 Key set *5.58099.012 **5.58099.013	 2 x 90° latching with stop	0	charcoal grey	3.13027.001
			dark grey	3.13027.201
			light beige	3.13027.401
			light grey	3.13027.501
		0 + 1 + 2	charcoal grey	3.13027.006
			dark grey	3.13027.206
			light beige	3.13027.406
			light grey	3.13027.506
	 3 x 90° latching with stop	0	charcoal grey	3.13027.011
			dark grey	3.13027.211
			light beige	3.13027.411
			light grey	3.13027.511
		0 + 1 + 2 + 3	charcoal grey	3.13027.016
			dark grey	3.13027.216
			light beige	3.13027.416
			light grey	3.13027.516


Rotary Switches IP 40

Rotary switch	Rotating angle	Colour	Order no.
(2)  Accessories: Adapter for 90° assembly 5.00642.008	 1 x 90° with stop	charcoal grey	3.13007.001
		dark grey	3.13007.201
		light beige	3.13007.401
		light grey	3.13007.501
	 2 x 90° with stop	charcoal grey	3.13007.011
		dark grey	3.13007.211
		light beige	3.13007.411
		light grey	3.13007.511
	 3 x 90° with stop	charcoal grey	3.13007.021
		dark grey	3.13007.221
		light beige	3.13007.421
		light grey	3.13007.521
	 4 x 90° without stop	charcoal grey	3.13007.031
		dark grey	3.13007.231
		light beige	3.13007.431
		light grey	3.13007.531

(1)

Hole pattern PCB (1), (2)
Component side

(2)



Standard locking position of the priority keylock switch (1) is 001, other locking positions on request.

Depending on the rotating angle 2 or 3 different keys are required. Two sets of keys are included in the delivery contents. Functioning: Key 1 can be switched till position 1, key 2 till position 1 and 2, etc.

Mechanical construction

Contact system

and arrangement: Cross contact, self-cleaning

Fixing: By soldering into the PCB

Flammability of

plastic materials: UL 94 HB

Contact material: Gold alloy

Terminals: 0.5 x 0.7 and 0.15 x 0.7, tin-plated

Lock characteristics (1):

Wafers: 5

Number of

locking positions: 500

Main key: Yes

Group key: Yes

General key: Yes

Symmetric key: No

Mechanical characteristics

Switching

positions: 4 max.

Key removal

positions (1): 4 max. (90° latching)

Actuating torque: 0.04...0.10 Nm

Robustness (1): ≥ 2 Nm

Torque till stop (2): > 0.45 Nm

Electrical characteristics

Rated voltage: 42 V max.

Rated current: 100 mA max.

Rated power: ≤ 1 W

Contact

resistance: ≤ 100 m Ω , when new

≤ 200 m Ω , after operating life

Insulation

resistance: $> 10^9$ Ω

ESD-strength: ≤ 8 kV

Dielectric

strength (1): > 500 V AC

Operating life:

(1): 5×10^4 operations

(2): 1×10^4 operations

Further details

Ambient temp.,

operating: -25 °C... $+70$ °C

Ambient temp.,

storage: -40 °C... $+80$ °C

Environment conditions:

- Constant environment: acc. to IEC 68-2-3 and 2-30

- Variable environment: acc. to IEC 68-2-14 and 2-33

Degree of

protection: (1) IP 54 according to DIN




(2) IP 40 according to DIN

Position	Contact function
0	
1	
2	
3	

Code Switches IP 40

Code switch	Colour	Order no.
	charcoal grey	3.13008.001
	dark grey	3.13008.201
	light beige	3.13008.401
	light grey	3.13008.501

Hole pattern
for terminals
in PCB –
component
side



Mechanical construction

Contact system: Self-cleaning sliding contacts
on PCB
Fixing: By soldering into the PCB
Flammability of
plastic materials: UL 94 HB
Contact material: Gold alloy
Terminals: Tin-plated

Mechanical characteristics

Torque for
actuation: < 0.03 Nm
Latching
positions: 16 x 22.5°

Electrical characteristics

Rated voltage: 2...42 V
Rated current: 0.01...100 mA
Rated power: 1 W max.
Contact
resistance: $\leq 100 \text{ m}\Omega$, when new
 $\leq 200 \text{ m}\Omega$, after operating life
Insulation
resistance: $> 10^{11} \Omega$
ESD-strength: $\leq 10 \text{ KV}$
Coding of
the outputs: Hexadecimal

Operating life: $\geq 1 \times 10^4$ operations

Further details

Ambient temp.,
operating: - 25 °C... + 70 °C
Ambient temp.,
storage: - 40 °C... + 80 °C
Environment conditions:
- Constant environment: acc. to IEC 68-2-3 and 2-30
- Variable environment: acc. to IEC 68-2-14 and 2-33
Degree of
protection: IP 40

Locking diagram



C connected to

	1	2	4	8
0				
1	●			
2		●		
3	●	●		
4			●	
5	●		●	
6		●	●	
7	●	●	●	
8				●
9	●			●
A		●		●
B	●	●		●
C			●	●
D	●		●	●
E		●	●	●
F	●	●	●	●


Switching
position


● Contact closed

7-Segment LED Displays

7-Segment LED display	Version	Order no.
(1) 	Common cathode	5.93005.060
	Common anode	5.93005.048
 Pin assignment Pin 1 Segment E 2 Segment D 3 Anode 4 Segment C 5 Decimal point 6 Segment B 7 Segment A 8 Anode 9 Segment F 10 Segment G  Character height: 14 mm Colour: red, 635 nm Light intensity: typ. 1700 µcd at $I_F = 10$ mA/segment Forward voltage at $I_F = 20$ mA: typ. 2.1 V Forward current max.: 25 mA/segment Current reduction: approx. 0.5 mA/°C from 50 °C on Ambient temp., operating: - 40 °C... + 85 °C		

7-Segment LED display		Version		Order no.
(2) 	Common cathode	1-digit	5.09300.011	
		2-digit	5.09300.012	
	Common anode	1-digit	5.09300.021	
		2-digit	5.09300.022	





Pin assignment

Pin

- 1 Cathode/Anode
- 2 Segment F
- 3 Segment G
- 4 Segment E
- 5 Segment D
- 6 Cathode/Anode
- 7 Decimal point
- 8 Segment C
- 9 Segment B
- 10 Segment A



Character height: 9.20 mm

Colour: red, typ. 635 nm at $I_F = 20$ mA

Light intensity: typ. 2000 μ cd at $I_F = 10$ mA/segment

Forward voltage: typ. 2.1 V at $I_F = 20$ mA/segment

Reverse voltage: 5 V/segment

Forward current: 25 mA/segment

Reverse current: 100 μ A max./segment

Current reduction: 0.33 mA approx./ $^{\circ}$ C from 25 $^{\circ}$ C on

Ambient temperature, operating: - 35 $^{\circ}$ C... + 85 $^{\circ}$ C

Solder temperature 1/16 inch below seating plane for 3 seconds at 260 $^{\circ}$ C